

[Close](#)[Print](#) [1]**Record 1 of 1****Title:** Supercontinuum generation from a sub-megahertz repetition rate femtosecond pulses based on nonlinear polarization rotation technique**Author(s):** Ahmad, H (Ahmad, H.); Ismail, MF (Ismail, M. F.); Hassan, SNM (Hassan, S. N. M.); Muhammad, FD (Muhammad, F. D.); Zulkifli, MZ (Zulkifli, M. Z.); Harun, SW (Harun, S. W.)**Source:** JOURNAL OF MODERN OPTICS **Volume:** 61 **Issue:** 16 **Pages:** 1333-1338 **DOI:** 10.1080/09500340.2014.931478 **Published:** 2014**Times Cited in Web of Science Core Collection:** 0**Total Times Cited:** 0**Cited Reference Count:** 22

Abstract: A means of supercontinuum (SC) generation is proposed and demonstrated, using femtosecond mode-locked pulses with sub-megahertz repetition rate based on the nonlinear polarization rotation technique. Total cavity length is approximately 522 m, which includes an additional 500 m single mode fiber (SMF) and the fundamental repetition rate obtained is 404.5 kHz. The mode-locked spectrum has a central wavelength of approximately 1600 nm and a 3 dB bandwidth of 16 nm, which falls within the L-band region. The threshold power for the mode-locked operation is achieved at approximately 52mW. At pump power of 74mW, the measured pulse width, pulse energy, and average output power are 70 fs, 18.3 nJ and 7.4mW respectively. The generated pulses are amplified by a 72.44mW erbium-doped fiber amplifier before being injected into a 100 m long highly non-linear fiber as the nonlinear medium to generate the SC spectrum. The obtained SC spectrum spans from 1250 nm to more than 1700 nm, with bandwidths of 450 nm at a -70 dBm output power level. For comparison purpose, the 500 m SMF is removed from the setup and similar measurements are then repeated for this case.

Accession Number: WOS:000341023500006**Language:** English**Document Type:** Article**Author Keywords:** supercontinuum; femtosecond pulse; mode-locked fiber laser; nonlinear polarization; rotation**KeyWords Plus:** LOCKED FIBER LASER; HIGH-ENERGY PULSES; MODE-LOCKING; RING LASER; CAVITY**Addresses:** [Ahmad, H.; Ismail, M. F.; Hassan, S. N. M.; Muhammad, F. D.; Zulkifli, M. Z.; Harun, S. W.] Univ Malaya, Dept Phys, Photon Res Ctr, Kuala Lumpur 59100, Malaysia.**Reprint Address:** Ahmad, H (reprint author), Univ Malaya, Dept Phys, Photon Res Ctr, Kuala Lumpur 59100, Malaysia.**E-mail Addresses:** harith@um.edu.my**Publisher:** TAYLOR & FRANCIS LTD**Publisher Address:** 4 PARK SQUARE, MILTON PARK, ABINGDON OX14 4RN, OXON, ENGLAND**Web of Science Categories:** Optics**Research Areas:** Optics**IDS Number:** AO0SY**ISSN:** 0950-0340**eISSN:** 1362-3044**29-char Source Abbrev.:** J MOD OPTIC**ISO Source Abbrev.:** J. Mod. Opt.**Source Item Page Count:** 6

Funding:

Funding Agency	Grant Number
ERGS Ministry of Education Malaysia	ER006-2013A
University of Malaya HIR Grant (Terahertz), MOHE	
	UM.C/625/1/HIR/MoHE/SC/29/01

We would like to thank ERGS Ministry of Education Malaysia (ER006-2013A) and University of Malaya for providing the HIR Grant (Terahertz), MOHE and UM.C/625/1/HIR/MoHE/SC/29/01 for funding this project.

[Close](#)

Web of Science™
Page 1 (Records 1 -- 1)

[Print](#)

◀ [1] ▶